



## FX-20 moisture meter for hay producers looking to enhance quality control

The FX-20 is the newest in the legendary "F Series" pin meters for checking hay moisture in the windrow or in bales. This rugged meter has an ergonomic design with an easy grip handle and large tactile buttons for comfort and usability. Equipped with a custom, LCD display and intuitive user interface, users can quickly obtain accurate readings. The FX-20 will ensure maximum performance and reliability on every job.



### FX-20 PRODUCT FEATURES

- Large, custom display with auto backlight – easy to read under all conditions
- Modern case design with large, tactile buttons and E-Z grip handle
- On-screen statistics for up to 100 readings saved to the meter
  - High, Low, Average, Standard Deviation
- Moisture Range:
  - Hay 6%-40%
- Alarm set point - alerts to user-selected MC level
- Internal calibration check
- "Low Batt" warning with audio
- Auto off timer. Set to 1m, 4m or 10m
- Compatible with existing Delmhorst prods and electrodes

### METER SPECIFICATIONS

- Power: 2x AA Alkaline batteries
- Temperature Correction Range: -18°->124°C
- QR code on meter for easy access to support materials and meter registration
- Size: meter only - 20.40cm x 7.24cm x 4.06cm
- Weight: meter only – 218 g
- Optional hard plastic carrying case
- 2-year limited warranty on manufacture's defects. Bonus warranty with on-line registration

### FX-20 Package Variations:

**The FX-20**, purchased individually, includes the FX-20 meter only. **Order as FX-20**

**The Value Package** includes the FX-20 meter and 1235 25 cm prod. **Order as FX-20/1235**

**The Value 18" Package** includes the FX-20 meter, and 1235/18 45 cm prod. **Order as FX-20/1235/18**

**The Deluxe Package** includes the FX-20 meter, 324CAS-0112 carrying case, H-4 handle, 830-2 35 cm prod, and 831 windrow probe. **Order as FX-20/P01**



## FX-20 moisture meter for hay producers looking to enhance quality control

### Recommended electrodes:



#### 1235

Pen electrode available in 2 lengths:

1235 – 25cm (10")

1235/18 – 45cm (18")

(Attaches directly to the connector on top of the meter)

For moisture measuring in standard bales



#### 830-X

Pen electrode available in different lengths:

830-2 – 25cm (10")

830-3 – 45cm (18")

830-4 – 90cm (36")

(Requires H-4 Handle)

For moisture measuring in standard and high density bales



#### 831

Short needle electrode (requires H-4 Handle)

For testing MC of hay in the windrow



#### H-4

Handle for electrodes 830-x and 831.

Two handed operation is recommended over using an electrode that connects directly to the top of the meter (like our 1235 series) to minimize stress placed on the meter casing.



#### MCS-5

This moisture content standard is great for verifying that your F-series moisture meter is in calibration. With two electrical resistance values (16% and 22%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy.